AKDO

ORIGAMI MASSUGU CREAM TAUPE (P) W/ COCOA TAUPE (P) *Stone, Marble*



PART NUMBER	PROFILE	AVAILABILITY
MB1716-MASS00	MOSAIC	SPECIAL ORDER
GROUT JOINT	**DIMENSIONS**	**THICKNESS**
1/16"	Set Size 11.50″ x 13.75″ = 1.10 sqft	3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot. cream taupe may be used in wet areas (walls only) when sealed correctly. two coats of penetrating sealer are recommended.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND	INTERIOR
Yes	Yes	Standard Commercial	No	No	Wall Only	No	Yes	Yes	Yes

Cream Taupe is a moisture sensitive stone.

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A.137.1	Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance. In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.