

## ARCADIA GRAIN EBONY (M)

## Porcelain

PART NUMBER
PO2383-GRAI00

PROFILE TILE REPEAT

48

AVAILABILITY

GROUT JOINT

DIMENSIONS

SPECIAL ORDER

1/8"

3.86'' x 18.31'' = .491 sqft

THICKNESS

3/8"

**ORIGIN** 

Spain

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

## APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Residential	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION		
Abrasion Resistance - ISO 10545-7	Residential PEI 2	Breaking Strength - ISO 10545-4	> 1300 N		
Chemical Resistance - ISO 10545-13	GLA	Coefficient of Thermal Linear Expansion - ISO 10545-8	< 9*10-6 1/4C-1		
Crazing Resistance - ISO 10545-11	Resistant	Frost Resistance - ISO 10545-12	Resistant		
Heat Resistance - 96/603/CE	A1-A1FL	Bending Resistance - ISO 10545-4	> 35N/mm_		
Water Absorption - ISO 10545-3	> 0.5%				
TECHNICAL DATA					
FEATURES & STANDARD	SPECIFICATION				

> 0.47

akdo.com

DCOF - ANSI A. 137. 1