# AKDO

## EMPERADOR MOKA (P) <sup>3</sup>/<sub>4</sub> SLAB Stone, Marble



PART NUMBER MB2088-SL34PO	profile <b>Slab</b>	availability Special order					
THICKNESS 3/4"							
NOTES Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.							

#### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes FIREPLAC SURROL		Standard Commercial INTERIOR	Yes	YES - when properly sealed	YES - when properly sealed	No	Yes
Yes		Yes					

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### **TECHNICAL DATA**

#### FEATURES & STANDARD

DCOF - ANSI A.137.1

#### SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.