

INDUSTRY 12" X 24" STONE CRATER (M) Porcelain



PART NUMBER

PROFILE TILE AVAILABILITY

FACTORY OUTLET

PO2297-1224M0 GROUT JOINT

11111

THICKNESS

1/16"

11.81" x 23.62" = 1.94 sqft

DIMENSIONS

3/8"

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Standard Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Breaking Strength - ISO 10545-4	R >= 35N/mm2	Crazing Resistance - ISO 10545-11	Pass
Frost Resistance - ISO 10545-11	Pass	Regularity of Length & Width - ISO 10545-2	300 x 600mm +/- 0.6mm
Resistance to Household Chemicals - ISO 10545-13	GA	Resistance to Swimming Pool Salts - ISO 10545-13	GA
Water Absorption - ISO 10545-3	0.03%		
TECHNICAL DATA			
FEATURES & STANDARD	SPECIFICATION		
DCOF - ANSI A. 137. 1	0.43		