

WIDE STEEL 3-1/2X24 LISTONE WAVE Porcelain

PART NUMBER

PROFILE

AVAILABILITY

PO2134-LSWV00

TILE

AVAILABLE ON REQUEST

GROUT JOINT

1/16"

DIMENSIONS

3.50" x 24.00" = .390 sqft

THICKNESS

3/8"

ORIGIN

Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND	INTERIOR
Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installar for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION				
Water Absorption - ISO 10545-3	0.2%	TECHNICAL DATA			
Resistance to Swimming Pool Salts - ISO 10545-13	Compliant	Surface Flatness - ISO 10545-2	Compliant		
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	Compliant		
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant		
Bending Resistance - ISO 10545-4	Compliant	Reaction to Fire - EN 13501-1	Alfl		
Frost Resistance - ISO 10545-12	Compliant	Impact Resistance - ISO 10545-5	Compliant		
Coefficient of Thermal Linear Expansion - ISO 10545-8	² 7_MK-1	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0.40, Bagnato > 0.40		
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant		
FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION		

FEATURES & STANDARD

> 0.42 Wet

DCOF - ANSI A. 137.1

LEED

EQ112

Low-Emitting Materials Recycled Content

Zero

V.O.C.

20% pre-consumer recycled material