

The AKDO logo is positioned at the top center of the page. The background of the entire page is a complex, monochromatic pattern of interlocking geometric shapes, primarily hexagons and triangles, each containing intricate, traditional-style motifs such as floral and paisley designs. The overall aesthetic is one of sophisticated, vintage-inspired ornamentation.

AKDO®

HERITAGE

*Ornamental. Enduring. Dramatic.
Vintage style with contemporary flair.*

Far Beyond the Surface



Hexagon



Heritage Hexagon Black (M)
PO1902-HEXA00



Heritage Hexagon Ash (M)
PO1900-HEXA00



Heritage Hexagon Birch White (M)
PO1901-HEXA00



Heritage Hexagon Highland Pattern (M)
PO1903-HEXA00





Heritage Hexagon Blend 1 (M)
PO1901-HEXA01



Heritage Hexagon Blend 2 (M)
PO1902-HEXA01



CONVERSION CHART

PROFILE	SIZE
Hexagon	10.60" x 9.00" = .494 sqft

APPLICATIONS

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL
Yes	Yes	Yes	Yes	Yes	Yes	Yes

TECHNICAL DATA

DIMENSIONS	STANDARD	REQUIRED STANDARD	MEAN VALUE
Length and Width	UNI-EN ISO 10545-2	± 0.6%	Compliant
Thickness	UNI-EN ISO 10545-2	± 1.5%	Compliant
Straightness of Sides	UNI-EN ISO 10545-2	± 0.5%	Compliant
Rectangularity	UNI-EN ISO 10545-2	± 0.5%	Compliant
Surface Flatness	UNI-EN ISO 10545-2	± 0.5%	Compliant
BENDING STRENGTH			
Breaking of Rupture	UNI-EN ISO 10545-4	> 1300 N (≥ 7.5mm) > 700 N (< 7.5mm)	Compliant
Modulus of Rupture	UNI-EN ISO 10545-4	> 35 N/mm ² (≥ 7.5mm)	Compliant
Resistance to Abrasion of Glazed Tiles	UNI-EN ISO 10545-7	-	Class 4 Light Colors Class 3 Dark Colors
Resistance to Deep Abrasion	UNI-EN ISO 10545-6	≤ 175mm ³	-
Scratch Resistance (MOHS)	EN 101	-	≥ 5
Water Absorption	UNI-EN ISO 10545-3	≤ 0.5%	Compliant
Slip Resistance (Ramp Test)	DIN 51130	-	R9
	DIN 51097	-	CLASS A
Slip Resistance (Pendulum Test)	UNI ENV 12633	-	CLASS 1
Colour Resistance to Light	DIN 510914	-	Resistant
Linear Thermal Expansion Coefficient (100o C)	UNI-EN ISO 10545-8	Test Method Available	Test Method Available
Resistance to Thermal Shock	UNI-EN ISO 10545-9	-	Resistant
Crazing Resistance	UNI-EN ISO 10545-11	-	Resistant
Frost Resistance	UNI-EN ISO 10545-12	-	Resistant
Chemical Resistance	UNI-EN ISO 10545-13	GB MIN.	Guaranteed (GA GLA GHA)
Resistance to Stains	UNI-EN ISO 10545-14	CLASS 3 MIN.	Class 5
Lead and Cadmium Given Off	UNI-EN ISO 10545-15	Test Method Available	Test Method Available
Coefficient of Friction	ASTM C-1028	-	-
Reaction to Fire	EN 13501-1	-	A1 _{FL} -A1

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

For detailed installation guidelines, visit akdo.com.

AKDO

1435 State Street
Bridgeport, CT 06605
1.800.811.2536
203.336.5199 (o)
203.336.0603 (f)

AKDO NYC

22 West 21st Street
New York, NY 10010
1.800.811.2536
212.485.0448 (o)
212.485.0449 (f)

AKDO Pacific

3445 Arden Road
Hayward, CA 94545
1.888.909.2536
510.785.2536 (o)
510.785.0895 (f)

akdo.com