

The AKDO logo is positioned at the top center of the image. It consists of the word "AKDO" in a clean, white, sans-serif font, with a registered trademark symbol (®) to its upper right. The background is a close-up of large, rectangular tiles with a light beige and grey marbled pattern, separated by dark grey grout lines. In the bottom left corner, a portion of a burlap sack containing a folded white fabric is visible.

AKDO®

NEW MARBLE

Far Beyond the Surface

NEW MARBLE

Coastal Gray



12" x 24" Coastal Gray (H)

MB2568-1224H1



12" Narrow Liner Coastal Gray (H)

MB2568-NL12H0



12" x 24" Waving Wood (H)

MB2357-1224H1



12" Narrow Liner Waving Wood (H)

MB2357-NL12H0



Product shown: 12" x 24" Waving Wood (H)



NEW MARBLE

Lilac



12" x 24" Lilac

(H) MB1053-1224H1

(P) MB1053-1224P1



4" x 12" Lilac

(H) MB1053-0412H0

(P) MB1053-0412P0



3" x 9" Lilac

(H) MB1053-0309H0

(P) MB1053-0309P0



12" Narrow Liner Lilac

(H) MB1053-NL12H0

(P) MB1053-NL12P0





NEW MARBLE

Moss Green



12" x 24" Moss Green (H)

MB1088-1224H1



12" Narrow Liner Moss Green (H)

MB1088-NL12H0



CONVERSION CHART

PROFILE	SIZE
3" x 9"	2.875" x 9" = .18 sqft (+/-)
4" x 12"	4" x 12" = .333 sqft (+/-)
12" x 24"	12" x 24" = 2 sqft (+/-)
Narrow Liner	11 9/16" x 1/2" = 1 LNFT

APPLICATIONS

Waving Wood Lilac	WALL	FLOOR	EXTERIOR FREEZE/ THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
	Yes	Yes	Yes	Yes, when properly sealed	Yes, when properly sealed	No	Yes
	FIREPLACE SURROUND	INTERIOR	TRAFFIC				
	Yes	Yes	Standard Commercial				
Coastal Gray	WALL	FLOOR	EXTERIOR FREEZE/ THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
	Yes	Yes	No	Yes, when properly sealed	Yes, when properly sealed	No	Yes
	FIREPLACE SURROUND	INTERIOR	TRAFFIC				
	Yes	Yes	Standard Commercial				
Moss Green	WALL	FLOOR	EXTERIOR FREEZE/ THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
	Yes	Yes	Yes	Yes, when properly sealed	Yes, when properly sealed	No	Yes
	FIREPLACE SURROUND	INTERIOR	TRAFFIC				
	Yes	Yes	Light Commercial				

TECHNICAL DATA

FEATURES	SPECIFICATION
DCOF – ANSI A.137.1	Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.
	To reduce the slipperiness of stone surfaces, AKDO suggests selecting a non-polished finish such as honed, sandblasted, or textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot. For detailed installation guidelines, visit akdo.com.

Product shown: 12" x 24" Waving Wood (H)

AKDO

1435 State Street
Bridgeport, CT 06605
1.800.811.2536
203.336.5199 (o)
203.336.0603 (f)

AKDO NYC

22 West 21st Street
New York, NY 10010
1.800.811.2536
212.485.0448 (o)
212.485.0449 (f)

AKDO Pacific

3445 Arden Road
Hayward, CA 94545
1.888.909.2536
510.785.2536 (o)
510.785.0895 (f)

akdo.com