## **AKDO**°

## CHEVRON POWDER (C) Glass



PART NUMBER PROFILE AVAILABILITY

GL1771-CHEVCO MOSAIC AVAILABLE ON REQUEST

GROUT JOINT DIMENSIONS THICKNESS

1/8" 10.75"  $\times 8.25$ " = .614 sqft (+/-) 5/16"

NOTES

 $\label{eq:decomposition} \mbox{Due to the inherent characteristics of glass there may be variations in color, movement and texture from lot to lot.}$ 

## APPLICATION AREA

| WALL | FLOOR | EXTERIOR | STEAM<br>SHOWER | WET<br>R AREA | POOL | BACKSPLASH                      | fireplace<br>Surround           | INTERIOR |
|------|-------|----------|-----------------|---------------|------|---------------------------------|---------------------------------|----------|
| Yes  | No    | Yes      | Yes             | Yes           | No   | YES - Heat not to exceed 1472°F | YES - Heat not to exceed 1472°F | Yes      |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

FEATURES & STANDARD SPECIFICATION

DCOF - ANSI A.137.1