

CURVE LINER PARCHMENT (F) *Glass*



| | | |
|---------------|--------------------------|----------------------|
| PART NUMBER | PROFILE | AVAILABILITY |
| GL1696-CL12FN | TRIM | AVAILABLE ON REQUEST |
| GROUT JOINT | DIMENSIONS | THICKNESS |
| 1/8" | .38" x 11.75" = .980 lmf | 5/16" |

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot. When using mosaics containing mirror in a backsplash design, include a 4" splash guard of wet area appropriate material in areas where water may pool, such as behind faucets.

APPLICATION AREA

| | | | | | | | | |
|------|-------|----------|-----------------|-------------|------|------------------------------------|------------------------------------|----------|
| WALL | FLOOR | EXTERIOR | STEAM SHOWER | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND | INTERIOR |
| Yes | No | Yes | Yes | Yes | Yes | YES - Heat not to exceed 1472°F | YES - Heat not to exceed 1472°F | Yes |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A.137.1

SPECIFICATION

0.28