

HERITAGE HEXAGON ASH (M) *Porcelain*



|               |                            |              |
|---------------|----------------------------|--------------|
| PART NUMBER   | PROFILE                    | AVAILABILITY |
| PO1900-HEXA00 | TILE                       | IN STOCK     |
| GROUT JOINT   | DIMENSIONS                 | THICKNESS    |
| 1/8"          | 10.60" x 9.00" = .494 sqft | 3/8"         |
| ORIGIN        |                            |              |
| Italy         |                            |              |

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

|          |       |                  |          |                 |             |      |            |                       |
|----------|-------|------------------|----------|-----------------|-------------|------|------------|-----------------------|
| WALL     | FLOOR | TRAFFIC          | EXTERIOR | STEAM<br>SHOWER | WET<br>AREA | POOL | BACKSPLASH | FIREPLACE<br>SURROUND |
| Yes      | Yes   | Light Commercial | Yes      | Yes             | Yes         | Yes  | Yes        | Yes                   |
| INTERIOR |       |                  |          |                 |             |      |            |                       |
| Yes      |       |                  |          |                 |             |      |            |                       |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

| FEATURES & STANDARD                        | SPECIFICATION                  | FEATURES & STANDARD                                   | SPECIFICATION                                  |
|--|--------------------------------|---|--|
| Abrasion Resistance - ISO 10545-7          | Class 4                        | Slip Resistance - UNI ENV 12633                       | Class 1  |
| Barefoot Ramp Test - DIN 51097             | Class A                        | Breaking Strength - ISO 10545-4                       | > 1300 N († 7.5mm) > 700 N (‡ 7.5mm) Compliant |
| Chemical Resistance - ISO 10545-13         | Guaranteed (GA GIA GHA)        | Coefficient of Thermal Linear Expansion - ISO 10545-8 | Test Method Available                          |
| Crazing Resistance - ISO 10545-11          | Resistant                      | Frost Resistance - ISO 10545-12                       | Resistant                                      |
| Bending Resistance - ISO 10545-4           | > 35 N/mm2 († 7.5mm) Compliant | Scratch Resistance (MOHS) - EN 101                    | 35   |
| Reaction to Fire - EN 13501-1              | A1 FL-A1                       | Regularity of Length & Width - ISO 10545-2            | ± 0.6% Compliant                               |
| Regularity of Rectangularity - ISO 10545-2 | ± 0.5% Compliant               | Regularity of Straightness of Sides - ISO 10545-2     | ± 0.5% Compliant                               |
| Surface Flatness - ISO 10545-2             | ± 0.5%                         | Water Absorption - ISO 10545-3                        | ² 0.5% Compliant                               |
| Colour Resistance to Light - DIN 510914    | Resistant                      | Lead and Cadmium Given Off - UNH EN ISO 10545-15      | Test Method Available                          |
| FEATURES & STANDARD                        | SPECIFICATION                  | TECHNICAL DATA  |  |
| DCOF - ANSI A.137.1                        | > 0.42 (actual score .68)      |   |  |

