


TRAPEZOID HERITAGE BIRCH WHITE *Porcelain*

	PART NUMBER	AVAILABILITY	GROUT JOINT
	PO1901-TRAP00	AVAILABLE ON REQUEST	1/8"
	DIMENSIONS	THICKNESS	ORIGIN
	1pc=0.247sqft	3/8"	Italy
NOTES			
Available nationwide.			
Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.			

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes
INTERIOR								
Yes								

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	Class 4	Slip Resistance - UNI ENV 12633	Class 1
Barefoot Ramp Test - DIN 51097	Class A	Breaking Strength - ISO 10545-4	> 1300 N (P 7.5mm) > 700 N (c 7.5mm) Compliant
Chemical Resistance - ISO 10545-13	Guaranteed (GA GLA GHA)	Coefficient of Thermal Linear Expansion - ISO 10545-8	Test Method Available
Crazing Resistance - ISO 10545-11	Resistant	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ISO 10545-4	> 35 N/mm2 (P 7.5mm) Compliant	Scratch Resistance (MOHS) - EN 101	³5
Reaction to Fire - EN 13501-1	A1 FL-A1	Regularity of Length & Width - ISO 10545-2	± 0.6% Compliant
Regularity of Rectangularity - ISO 10545-2	± 0.5% Compliant	Regularity of Straightness of Sides - ISO 10545-2	± 0.5% Compliant
Surface Flatness - ISO 10545-2	± 0.5%	Water Absorption - ISO 10545-3	² 0.5% Compliant
Colour Resistance to Light - DIN 510914	Resistant	Lead and Cadmium Given Off - UN/EN ISO 10545-15	Test Method Available
FEATURES & STANDARD	SPECIFICATION	TECHNICAL DATA	
DCOF - ANSI A.137.1	> 0.42 (actual score .68)		