

HERITAGE HEXAGON BLEND 1 (M) *Porcelain*



PART NUMBER
PO1901-HEXA01

PROFILE
TILE

AVAILABILITY
IN STOCK

GROUT JOINT
1/8"

DIMENSIONS
10.60" x 9.00" = .494 sqft

THICKNESS
3/8"

ORIGIN
Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Slip Resistance - UNI ENV 12633	Class 1	Barefoot Ramp Test - DIN 51097	Class A
Breaking Strength - ISO 10545-4	> 1300 N († 7.5mm) > 700 N († 7.5mm) Compliant	Chemical Resistance - ISO 10545-13	Guaranteed (GA GIA GHA)
Coefficient of Thermal Linear Expansion - ISO 10545-8	Test Method Available	Crazing Resistance - ISO 10545-11	Resistant
Frost Resistance - ISO 10545-12	Resistant	Bending Resistance - ISO 10545-4	> 35 N/mm ² († 7.5mm) Compliant
Scratch Resistance (MOHS) - EN 101	35	Reaction to Fire - EN 13501-1	A1 FL-A1
Regularity of length & Width - ISO 10545-2	± 0.6% Compliant	Regularity of Rectangularity - ISO 10545-2	± 0.5% Compliant
Regularity of Straightness of Sides - ISO 10545-2	± 0.5% Compliant	Surface Flatness - ISO 10545-2	± 0.5%
Water Absorption - ISO 10545-3	≤ 0.5% Compliant	Colour Resistance to Light - DIN 510914	Resistant
Lead and Cadmium Given Off - UNI-EN ISO 10545-15	Test Method Available	TECHNICAL DATA	
FEATURES & STANDARD	SPECIFICATION		
DCOF - ANSI A.137.1	> 0.42 (actual score .68)		