AKDO

PLAZA NUEVA VEDADO NAVY (M) Porcelain



PART NUMBER PROFILE AVAILABILITY PO2590-070700 TILE **REGULAR STOCK** GROUT JOINT DIMENSIONS THICKNESS 1/16" 3/8" 7.28" X 7.28" = .368 SQFT ORIGIN Spain

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	Fireplace Surround
Yes	Yes	Light Residential	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD		Specification	FEATURES & STANDARD	Specification
Chemical Resistance - ISO 10545-13		GLA	Crazing Resistance - ISO 10545-11	Resistant
Frost Resistance - ISO 10545-12		Resistant	Resistance to Household Chemicals - ISO 10545-13	GA
Resistance to Swimming Pool Salts - ISO 10545-13		GA	Water Absorption - ISO 10545-3	Eb ² 0.5%
Pei Rating		Group 2		
TECHNICAL DA	TA			
FEATURES & STANDARD		SPECIFICATION		
DCOF - ANSI A. 1 37. 1		> 0.42		
LEED				
EQ	MR			
Low Emitting Materia	Is Material Ingredient Optim	ization		
No YOCs emission Compliant with the Restrictions of Reach and are listed on the candidate list.			the SVHC COMMERCIAL · HOSPITA	ality · residential