

## CONCRETE JUNGLE 24" X 24" X 3/4" ATELIER PAVER (T) *Porcelain*



|                              |           |               |
|------------------------------|-----------|---------------|
| PART NUMBER                  | PROFILE   | AVAILABILITY  |
| PO2522-2424GR                | PAVERS    | SPECIAL ORDER |
| DIMENSIONS                   | THICKNESS | ORIGIN        |
| 23.64" x 23.64" = 3.875 sqft | 3/4"      | Italy         |

### NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

|      |       |                        |          |                 |             |      |            |                       |
|------|-------|------------------------|----------|-----------------|-------------|------|------------|-----------------------|
| WALL | FLOOR | TRAFFIC                | EXTERIOR | STEAM<br>SHOWER | WET<br>AREA | POOL | BACKSPLASH | FIREPLACE<br>SURROUND |
| Yes  | Yes   | Standard<br>Commercial | Yes      | Yes             | Yes         | Yes  | Yes        | Yes                   |

### INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

| FEATURES & STANDARD                        | SPECIFICATION        | FEATURES & STANDARD                               | SPECIFICATION      |
|--|----------------------|---|--------------------|
| Abrasion Resistance - ISO 10545-6          | 145mm <sup>3</sup>   | Breaking Strength - ISO 10545-4                   | 13600N             |
| Chemical Resistance - ISO 10545-13         | LA, HA Resistant     | Shade Variation - ANSI A 137.1                    | V3                 |
| Frost Resistance - ISO 10545-12            | Resistant            | Fire Reaction - EN 9239-1                         | Class A1fl (floor) |
| Fire Reaction - EN 13823                   | Class A1 (wall)      | Regularity of Length & Width - ISO 10545-2        | Compliant          |
| Regularity of Rectangularity - ISO 10545-2 | Compliant            | Regularity of Straightness of Sides - ISO 10545-2 | Compliant          |
| Regularity of Thickness - ISO 10545-2      | Compliant            | Resistance To Staining - ISO 10545-14             | 5 Resistant        |
| Slip Resistance - ANSI A326.3              | DCOF ≥ 0.42          | Slip Resistance (Ramp Test) - DIN 51130           | R11                |
| Water Absorption - ISO 10545-3             | 0,05 %               | Thermal Conductivity - EN 12524                   | □ = 1,3 W/m °K     |
| Modulus of Rupture - ISO 10545-4           | 50 N/mm <sup>2</sup> |   |                    |

### LEED

|                                    |   |                        |                             |
|------------------------------------|---|------------------------|-----------------------------|
| MR                                 | MR  | EQ                     | ID                          |
| Recycled Content                   | Environmental Product Declaration                               | Low Emitting Materials | Innovation & Design         |
| 40% Pre-Consumer Recycled Material | Available industry-wide Environmental Product Declaration (EPD) | No VOCs Emission       | Certificate Greenguard GOLD |