

# MASON 24" X 48" IVORY (SOFT) Porcelain



PART NUMBER PROFILE REPEAT PO2465-2448ST TILE 40

AVAILABILITY GROUT JOINT DIMENSIONS

REGULAR STOCK 1/16" 23.62" x 47.24" = 7.748 sqft

THICKNESS ORIGIN
10mm Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

WALL	FLOOR	EXTERIOR	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND	INTERIOR
Yes	Yes	No	No	No	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

#### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	140	Barefoot Ramp Test - DIN 51097	А
Breaking Strength - ISO 10545-4	3200 N	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ISO 10545-4	50 N/mm2	Regularity of Length & Width - ISO 10545-2	± 0.15%
Regularity of Rectangularity - ISO 10545-2	± 0.2%	Regularity of Straightness of Sides - ISO 10545-2	± 0.1%
Surface Quality - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	UA
Resistance to Swimming Pool Salts - ISO 10545-13	UA	Booted Ramp Test - DIN 51130	R9
Surface Flatness - ISO 10545-2	± 0.35%	Water Absorption - ISO 10545-3	0.08%

## TECHNICAL DATA

FEATURES & STANDARD SPECIFICATION

DCOF - ANSI A.137.1 > 0.42 Wet

# LEED

MR	MR	MR	MR
Recycled Content	Regional Materials	Sustainability Report	Environmental Product Declaration
7,1%	38%	Available self-declared Corporate Sustainability Report (CSR) conform to Global Reporting Initiative (GRI) Sustainability Report	Available industry-wide Environmental Product Declaration (EPD) conform to ISO 14025

Material Ingredients

Available Health Product Declaration (HPD) in compliance with the Health Product Declaration Open Standard

Low Emitting Materials

Heat Island Effect

Energy Performance

akdo.com