

MASON 12" X 24" STEEL (SOFT) Porcelain



PART NUMBER PROFILE REPEAT PO2466-1224ST TILE 40

AVAILABILITY GROUT JOINT DIMENSIONS

REGULAR STOCK 1/16" 11.81" x 23.62" = 1.937 sqft

THICKNESS ORIGIN
10mm Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	EXTERIOR	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND	INTERIOR
Yes	Yes	No	No	No	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

LEED

		MR Sustainal	oility Report		MR Environmental Pro	MR Environmental Product Declaration	
13,9%	38%	Available self-declared Corporate Sustainability Report (CSR) Available industry-wide Environmental Proconform to Global Reporting Initiative (GRI) Sustainability Report Declaration (EPD) conform to ISO 14025					
MR Material Ingredients			EQ Low Emitting Materials	SS Heat Island Effect	EA Energy Performance	ID Innovatione & Design	
	uct Declaration (HPD) in a Declaration Open Standard		No VOCs Emission	Light Color SRI > 29	1,0 - 1,3 W/mK	Certificate Greenguard	