AKDO°

MASON 24" X 48" STEEL (SOFT)



Porcelain



Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

| WALL | FLOOR | WET AREA | POOL | BACKSPLASH | FIREPLACE SURROUND | INTERIOR |
|------|-------|-------------|------|------------|-----------------------|----------|
| Yes | Yes | No | No | Yes | Yes | Yes |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

LEED

| MR Recycled Content | MR Regional Materials | MR Sustainal | pility Report | MR Environmental Pro | MR Environmental Product Declaration | |
|----------------------------|--|--|------------------------------|--------------------------|---|----------------------------|
| 13,9% | | Available industry-wide Environmental Product Declaration (EPD) conform to ISO14025 | | | | |
| MR Material Ingredients | | | EQ Low Emitting Materials | SS Heat Island Effect | EA Energy Performance | ID Innovatione & Design |
| | luct Declaration (HPD) in a Declaration Open Standard | | No VOCs Emission | Light Color SRI > 29 | 1,0 - 1,3 W/mK | Certificate Greenguard |