

WIDE 12" X 24" CHALK (TEXTURED) Porcelain



PART NUMBER
PO2131-1224T1

PROFILE TILE AVAILABILITY
IN STOCK

DIMENSIONS

11.81" x 23.62" = 1.94 sqft

ORIGIN

Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWE	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

TECHNICAL DATA

FEATURES & CTANDARD	CDECIFICATION				
Water Absorption - ISO 10545-3	0.2%	TECHNICAL DATA			
Resistance to Swimming Pool Salts - ISO 10545-13	Compliant	Surface Flatness - ISO 10545-2	Compliant		
Regularity of Straightness of Sides - ISO 10545-2	Compliant	Resistance to Household Chemicals - ISO 10545-13	Compliant		
Regularity of Length & Width - ISO 10545-2	Compliant	Regularity of Rectangularity - ISO 10545-2	Compliant		
Bending Resistance - ISO 10545-4	Compliant	Reaction to Fire - EN 13501-1	Alfl		
Frost Resistance - ISO 10545-12	Compliant	Impact Resistance - ISO 10545-5	Compliant		
Coefficient of Thermal Linear Expansion - ISO 10545-8	² 7_MK-1	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0.40, Bagnato > 0.4		
Abrasion Resistance - ISO 10545-6	Compliant	Breaking Strength - ISO 10545-4	Compliant		
FEATURES & STANDARD	SPECIFICATION	features & standard	SPECIFICATION		

FEATURES & STANDARD

DCOF - ANSI A. 137.1

SPECIFICATION

> 0.42 Wet

LEED

SS110 EQ112

Heat Island Reduction Low-Emitting Materials

SRI>=33 Zero

Emissions

V.O.C.