
# **AKDO**°

## PENNY ROUNDS HEATHER (G)

### Porcelain



PART NUMBER
PO2511-PENYG0

PROFILE MOSAIC

AVAILABILITY IN STOCK

DIMENSIONS

11.57" x 12.40" = .996 sqft

#### APPLICATION AREA

| WALL | FLOOR | TRAFFIC             | EXTERIOR | STEAM<br>SHOWER | WET<br>R AREA | POOL | BACKSPLASH | FIREPLACE<br>SURROUND |
|------|-------|---------------------|----------|-----------------|---------------|------|------------|-----------------------|
| Yes  | Yes   | Heavy<br>Commercial | Yes      | Yes             | Yes           | Yes  | Yes        | Yes                   |

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installate for more information.

### TECHNICAL DATA

| FEATURES & STANDARD                              | SPECIFICATION | FEATURES & STANDARD                               | SPECIFICATION |
|--|---------------|---|---------------|
| Breaking Strength - ISO 10545-4                  | 812           | Crazing Resistance - ISO 10545-11                 | Pass          |
| Regularity of Rectangularity - ISO 10545-2       | -0.12~+0.11   | Regularity of Straightness of Sides - ISO 10545-2 | -0.12~+0.11   |
| Surface Quality - ISO 10545-2                    | Conformed     | Resistance to Household Chemicals - ISO 10545-13  | Class GA      |
| Resistance to Swimming Pool Salts - ISO 10545-13 | Class GA      | Modulus of Rupture - ISO 10545-4                  | 53 / 50~56    |