

GAJA SAND 2X2 MOSAIC (T) *Porcelain*



PART NUMBER
PO2415-0202T0

PROFILE
MOSAIC

AVAILABILITY
IN STOCK

DIMENSIONS
11.81" x 11.81" = .97 sqft

ORIGIN
Italy

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	Compliant	Barefoot Ramp Test - DIN 51097	A+B+C
Breaking Strength - ISO 10545-4	Compliant	Chemical Resistance - ISO 10545-13	Compliant
Coefficient of Thermal Linear Expansion - ISO 10545-8	≤ 7 10 ⁻⁶ •C ⁻¹	Coefficient of Friction - B.C.R.A. Rep. CEC/81	Asciutto > 0,40 / Bagnato > 0,40
DCOF - B.C.R.A. Rep. CEC-81	> 0.40	Frost Resistance - ISO 10545-12	Compliant
Coefficient of Restitution - ISO-10545-5	Compliant	Moisture Expansion - ISO 10545-10	≤ 0,01 %
Reaction to Fire - EN 13501-1	A1fl	Regularity of Length & Width - ISO 10545-2	Compliant
Resistance to Household Chemicals - ISO 10545-13	A	Resistance To Staining - ISO 10545-14	Class 5
Resistance to Swimming Pool Salts - ISO 10545-13	A	Booted Ramp Test - DIN 51130	R10
Slip Resistance (Ramp Test) - DIN 51130	R10	Thermal Shock Resistance - ISO 10545-9	Compliant
Water Absorption - ISO 10545-3	0.2%		

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION
DCOF - ANSI A.137.1	> 0.42 Wet