AKDO

RENAISSANCE 24" X 24" BELLA CANDIDO (P) *Porcelain*



PART NUMBER	PROFILE	AVAILABILITY
PO2323-2424P0	TILE	REGULAR STOCK
GROUT JOINT	**DIMENSIONS**	**THICKNESS**
1/16"	23.64'' x 23.64'' = 3.875 sqft	9mm
ORIGIN		
Italy		

NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

Renaissance is a popular choice for checkerboard layouts, however only certain colors within the collection can be paired together. please refer to the last page of the renaissance collection brochure for more information and consult your customer service representative to confirm caliber compatibility.

APPLICATION AREA

WALL	TRAFFIC	EXTERIOR	POOL	BACKSPLASH	FIREPLACE SURROUND	COUNTERTOP
Yes	Wall Only	Wall Only Including Freeze/Thaw	Yes	Yes	Yes	Yes

INTERIOR	SHOWER
Wall Only	Wall Only; Including Steam

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	Cl. 5	Breaking Strength - ISO 10545-4	Average Value 3200 N
Crazing Resistance - ISO 10545-11	Resistant	Frost Resistance - ISO 10545-12	Resistant
Bending Resistance - ISO 10545-4	Average Value 50 N/mm2	Regularity of Length & Width - ISO 10545-2	± 0,15%
Regularity of Rectangularity - ISO 10545-2	± 0,2%	Regularity of Straightness of Sides - ISO 10545-2	± 0,1%
Regularity of Thickness - ISO 10545-2	± 5%	Surface Quality - ISO 10545-2	Compliant
Resistance To Staining - ISO 10545-14	Cl. 4	Resistance to Swimming Pool Salts - ISO 10545-13	GA
Surface Flatness - ISO 10545-2	± 0,35%	Thermal Shock Resistance - ISO 10545-9	Resistant
Water Absorption - ISO 10545-3	Average Value 0,08%		