

SKYSCAPE 20" X 40" X 3/4" NIGHTFALL PAVER (T) Porcelain

Part Number

PROFILE

AVAILABILITY

PO2435-2040T0

PAVERS

AVAILABLE ON REQUEST

TECHNIC



THICKNESS

3/4"

NOTES

Available nationwide.

 $\label{eq:decomposition} \mbox{Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.}$

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

SPECIFICATION				
01 2011 107 11101 1	FEATURES & STANDARD	SPECIFICATION		
Compliant	Barefoot Ramp Test - DIN 51097	A+B+C		
S > 10000 N D R > 45 N/mm2	Chemical Resistance - ISO 10545-13	Compliant		
Compliant	Coefficient of Friction - B.C.R.A. Rep. CEC/81	>0.4		
Compliant	Regularity of Length & Width - ISO 10545-2	Compliant		
Compliant	Regularity of Straightness of Sides - ISO 10545-2	Compliant		
Compliant	Water Absorption - ISO 10545-3	2 0.1%		
SPECIFICATION				
	S > 10000 N D R > 45 N/mm2 Compliant Compliant Compliant Compliant	Compliant Coefficient of Friction - B.C.R.A. Rep. CEC/81 Compliant Regularity of Length & Width - ISO 10545-2 Compliant Regularity of Straightness of Sides - ISO 10545-2 Compliant Water Absorption - ISO 10545-3		

> 0.42

akdo.com

DCOF - ANSI A. 137. 1