

TRADITION 47" X 110" CALACATTA GUSTO (G) Porcelain



PART NUMBER PROFILE

PO2480-SL14G0 SLAB AVAILABLE ON REQUEST

AVAILABILITY

DIMENSIONS THICKNESS

47.24" x 110.24" = 36.16 sqft 6mm

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	<u> </u>	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL
Yes	Resider Use On	ntial Floor lly	Residential	Yes	Wall Only	Wall Only	Yes
BACKSPI	LASH	FIREPLACE SURROUND	INTERIOR				
Yes		Yes	Yes				

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
³ 1350 N	Frost Resistance - ISO 10545-12	Resistant
> 52 N/mm2	Regularity of Length & Width - ISO 10545-2	±0.15%
±0.2%	Regularity of Straightness of Sides - ISO 10545-2	±0.1%
Conforming	Surface Flatness - ISO 10545-2	±0.2%
0.08% (average)	TECHNICAL DATA	
SPECIFICATION		
	3 1350 N > 52 N/mm2 ±0.2% Conforming 0.08% (average)	3 1350 N Frost Resistance - ISO 10545-12 > 52 N/mm2 Regularity of Length & Width - ISO 10545-2 ±0.2% Regularity of Straightness of Sides - ISO 10545-2 Conforming Surface Flatness - ISO 10545-2 0.08% (average) TECHNICAL DATA

DCOF - ANSI A.137.1 > 0.42 wet