


## 16" X 24" TRUST GOLD *Porcelain*



PART NUMBER  
PO1692-162400

PROFILE  
TILE

AVAILABILITY  
SPECIAL ORDER

GROUT JOINT  
1/16"

DIMENSIONS  
1pc=40cm X 60cm=2.58sqft

THICKNESS  
3/8"

### NOTES

Available in northern ca, ct, de, me, ma, nv, nh, nj, ny, pa, ri, vt

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

### INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

#### FEATURES & STANDARD

Abrasion Resistance - ISO 10545-6

Breaking Strength - ISO 10545-4

Dynamic Friction Coefficient - METODO B.C.R.A.

Bending Resistance - ISO 10545-4

Regularity of Length & Width - ISO 10545-2

Regularity of Straightness of Sides - ISO 10545-2

Resistance to Swimming Pool Salts - ISO 10545-13

Booted Ramp Test - DIN 51130

Water Absorption - ISO 10545-3

#### SPECIFICATION

Suitable For

S<sup>3</sup> 1300 N

> 0.40

R<sup>3</sup> 35 N/mm<sup>2</sup>

± 0.1% ± 0.1%

± 0.1%

UA

R10-R12 GRIP

≈ 0.5%

#### FEATURES & STANDARD

Barefoot Ramp Test - DIN 51097

Coefficient of Thermal Linear Expansion - ISO 10545-8

Frost Resistance - ISO 10545-12

Scratch Resistance (MOHS) - EN 101

Regularity of Rectangularity - ISO 10545-2

Resistance to Household Chemicals - ISO 10545-13

SCOF - ASTM C1028-96

Surface Flatness - ISO 10545-2

#### SPECIFICATION

A+B+A+B+C GRIP

≈ 9 MK-1

Resistant

8

± 0.1%

UA

≈ 0.60 DRY ≈ 0.60 WET

Not applicable

### TECHNICAL DATA

#### FEATURES & STANDARD

DCOF - ANSI A.137.1

#### SPECIFICATION

>.42 (actual score .60)