

ARCADIA GRAIN OAK (M) *Porcelain*



PART NUMBER
PO2382-GRAI00

PROFILE
TILE

REPEAT
48

AVAILABILITY
IN STOCK

VARIATION
HIGH

GROUT JOINT
1/8"

DIMENSIONS
3.86" x 18.31" = .491 sqft

THICKNESS
3/8"

NOTES

Available nationwide.
Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Light Commercial	Yes	Yes	Yes	Yes	Yes	Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	Light Commercial PEI 3	Breaking Strength - ISO 10545-4	> 1300 N
Chemical Resistance - ISO 10545-13	GLA	Coefficient of Thermal Linear Expansion - ISO 10545-8	< 9*10-6 ¼C-1
Crazing Resistance - ISO 10545-11	Resistant	DCOF - ANSI A.137.1	> 0.47
Frost Resistance - ISO 10545-12	Resistant	Heat Resistance - 96/603/CE	A1-A1FL
Bending Resistance - ISO 10545-4	> 35N/mm_	Water Absorption - ISO 10545-3	> 0.5%