AKDO

ARCADIA GRAIN BEECH (M)



- D - 1	
Porcel	ain
101000	un



Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	Fireplace Surround
Yes	Yes	Standard Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information

TECHNICAL DATA

ATURES & STANDARD	SPECIFICATION
eaking Strength - ISO 10545-4	> 1300 N
pefficient of Thermal Linear Expansion - ISO 10545-8	< 9*10-6 ¼C-1
ost Resistance - ISO 10545-12	Resistant
ending Resistance - ISO 10545-4	> 35N/mm_
ec De	aking Strength - ISO 10545-4 officient of Thermal Linear Expansion - ISO 10545-8 t Resistance - ISO 10545-12

TECHNICAL DATA

FEATURES & STANDARD	SPECIFI
DCOF - ANSI A. 137.1	> 0.47

SPECIFICATION