

ARCHITETTO ANGOLO CARRARA BELLA (H) W/ STAINLESS STEEL Stone, Marble, Metal



PART NUMBER PROFILE AVAILABILITY

MB1604-ANGOH1 MOSAIC REGULAR STOCK

GROUT JOINT DIMENSIONS THICKNESS 1/16" 8" \times 8" = .444 sqft 3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL **FLOOR TRAFFIC EXTERIOR** STEAM WET POOL BACKSPLASH SHOWER AREA Stainless steel may Light Commercial YES - when properly YES - Heat not to scratch when used exceed 293° F as floor covering **FIREPLACE** INTERIOR SURROUND

YES - Heat not to exceed 293° F

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

Epoxy grout should be used when installing Architetto mosaics with metal.

TECHNICAL DATA

FEATURES & STANDARD

SPECIFICATION

DCOF - ANSI A. 137. 1

Dynamic Coefficient of Friction (DCOF) Testing Test Name: ANSI A137.1

Results: >.42