

ASH GRAY (P) 1 1/4" SLAB Stone, Marble



PART NUMBER PROFILE AVAILABILITY
MB1809-SL54P0 SLAB REGULAR STOCK

THICKNESS ORIGIN 1-1/4" Turkey

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM	WET	POOL	BACKSPLASH
VVALL	ILOOK	TRAITIC	LATERIOR	SHOWER	AREA	FOOL	BACKSFLASIT
				SHOVVER	AREA		
Yes	Yes	Standard	Yes	VEC .uban pranarlı	VEC when preparly	No	Yes
res	res	Commercial	res	YES - when properly sealed	YES - when properly sealed	140	res
FIREPLACE		INTERIOR					
SURROUND							
Yes		Yes					

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A. 137. 1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.