

## NUVOLA TAJ MAHAL (P) SLAB *Porcelain*



PART NUMBER  
PO2629-SL12P0

PROFILE  
SLAB

AVAILABILITY  
REGULAR STOCK

DIMENSIONS  
62.99" x 125.98" = 55.117 sqft

THICKNESS  
12mm

ORIGIN  
Italy

### NOTES

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH
Yes	Yes	Residential	Yes	Wall Only	Wall Only	Yes	Yes
FIREPLACE SURROUND	INTERIOR						
Yes	Yes						

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Chemical Resistance - ISO 10545-13	Resistant	Coefficient of Thermal Linear Expansion - ISO 10545-8	$\alpha 7.00 \text{ MK} [- 1]$
Frost Resistance - ISO 10545-12	Resistant	Regularity of Length & Width - ISO 10545-2	+/- 0.6%
Regularity of Rectangularity - ISO 10545-2	+/- 0.6%	Regularity of Straightness of Sides - ISO 10545-2	+/- 0.5%
Regularity of Thickness - ISO 10545-2	+/- 5%	Resistance To Staining - ISO 10545-14	Cl. 3
Surface Flatness - ISO 10545-2	+/- 0.5%	Thermal Shock Resistance - ISO 10545-9	Resistant
Water Absorption - ISO 10545-3	$\leq 0.5\%$	DCOF – ANSI A326.3:2019	> 0.42 Wet