

## TRADITION 47" X 110" CALACATTA GUSTO (M) Porcelain



PROFILE

AVAILABILITY

PO2480-SL14M0

SLAB

AVAILABLE ON REQUEST



DIMENSIONS

THICKNESS

47.24" x 110.24" = 36.16 sqft

6mm

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

## APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET R AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

## TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION			
Breaking Strength - ISO 10545-4	³ 1350 N	Frost Resistance - ISO 10545-12	Resistant			
Bending Resistance - ISO 10545-4	> 52 N/mm2	Regularity of Length & Width - ISO 10545-2	±0.15%			
Regularity of Rectangularity - ISO 10545-2	±0.2%	Regularity of Straightness of Sides - ISO 10545-2	±0.1%			
Surface Quality - ISO 10545-2	Conforming	Surface Flatness - ISO 10545-2	±0.2%			
Water Absorption - ISO 10545-3	0.08% (average)	TECHNICAL DATA				
FEATURES & STANDARD	SPECIFICATION	SPECIFICATION				

DCOF - ANSI A. 137. 1

> 0.42 wet