

TRADITION 47"X110" BEIGE MARFIL SLAB Porcelain



PART NUMBER PROFILE
PO2482-SL14G0 SLAB

SLAB

AVAILABLE ON REQUEST

DIMENSIONS 47.24" x 110.24" - 36.16 sqft THICKNESS

6mm

NOTES

Available nationwide.

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

WALL	FLOOF	R	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL
Yes	Resider Use Or	ntial Floor nly	Residential	Yes	Wall Only	Wall Only	Yes
BACKSP	LASH	FIREPLACE SURROUND	INTERIOR)	<u> </u>			
Yes		Yes	Yes				

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-7	140 mm3	Breaking Strength - ISO 10545-4	³ 1350 N
Frost Resistance - ISO 10545-12	Resistant	Bending Resistance - ISO 10545-4	> 52 N/mm2
Regularity of Length & Width - ISO 10545-2	±0.15%	Regularity of Rectangularity - ISO 10545-2	±0.2%
Regularity of Straightness of Sides - ISO 10545-2	±0.1%	Surface Quality - ISO 10545-2	Conforming
Resistance to Household Chemicals - ISO 10545-13	UA	Resistance to Swimming Pool Salts - ISO 10545-13	UA
Surface Flatness - ISO 10545-2	±0.2%	Water Absorption - ISO 10545-3	0.08% (average)
FEATURES & STANDARD	SPECIFICATION		

DCOF - ANSI A.137.1

> 0.42 wet

TECHNIC