

## LILY (P) 1 1/4" SLAB *Quartz*



PART NUMBER  
QZ1947-SL54P0

PROFILE  
SLAB

AVAILABILITY  
IN STOCK

DIMENSIONS

130.00" x 64.00" = 57.780 sqft (+/-)

THICKNESS

1-1/4"

### NOTES

Due to the inherent characteristics of quartz, there may be variations in color, movement and texture from lot to lot.

### APPLICATION AREA

WALL	FLOOR	TRAFFIC	EXTERIOR	STEAM SHOWER	WET AREA	POOL	BACKSPLASH	FIREPLACE SURROUND
Yes	Yes	Standard Commercial	No	Yes	Yes	No	Yes - Heat not to exceed 392° F	Yes - Heat not to exceed 392° F

### INTERIOR

Yes

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

### TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION	FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - EN 14617-4	28 mm (A4)	Density - EN 14617-1	2.34-2.40 gr/cm <sup>3</sup>
Chemical Resistance - EN 14617-10	C4	Flexural Strength - EN 14617-2	40-80 MPa (F4)
Frost Resistance - EN 14617-5	KMf25 = 97.8 %	Impact Resistance - EN 14617-9	> 3.4 Joule (20mm)
Reaction to Fire - EN 13501-1	A2fl s1	Water Absorption - EN 14617-1	< 0.05 % (W4)