

## 4" X 12" STRAIGHT EDGE TURKISH GRAY (P) *Stone, Marble*



PART NUMBER  
MB1266-0412P0

PROFILE  
TILE

AVAILABILITY  
AVAILABLE ON REQUEST

GROUT JOINT  
1/8"

DIMENSIONS  
4.00" x 12.00" = .333 sqft

THICKNESS  
3/8"

### NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

Micro pits or scratches may appear white, therefore using a complimentary gray grout is recommended.

It is important to properly seal marble used in a shower/steam shower, and maintain the sealant regularly to ensure water beads off the tile.

### APPLICATION AREA

| WALL                  | FLOOR | TRAFFIC                | EXTERIOR<br>FREEZE/THAW | STEAM<br>SHOWER               | WET<br>AREA                   | POOL | BACKSPLASH |
|-----------------------|-------|------------------------|-------------------------|-------------------------------|-------------------------------|------|------------|
| Yes                   | Yes   | Standard<br>Commercial | No                      | YES - when properly<br>sealed | YES - when properly<br>sealed | No   | Yes        |
| FIREPLACE<br>SURROUND |       |                        |                         |                               |                               |      |            |
| Yes                   |       |                        |                         |                               |                               |      |            |

The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.