

2" X 8" WHITE HAZE (H) Stone, Marble

PART NUMBER

PROFILE

AVAILABILITY

MB1741-0208H0

TILE

REGULAR STOCK

GROUT JOINT

DIMENSIONS

THICKNESS

1/8"

 $1.97'' \times 7.87'' = .108 \text{ sqft (+/-)}$

3/8"

NOTES

Due to the inherent characteristics of natural stone, there may be variations in color, movement and texture from lot to lot.

APPLICATION AREA

TRAFFIC EXTERIOR POOL **BACKSPLASH**

FIREPLACE SURROUND COUNTERTOP

INTERIOR

Commercial Non Freeze/Thaw; Wall Only

Wall and Floor

SHOWER

Wall and Floor; Including Steam

DISCLAIMER: The performance of surface covering products often depends on installation, environmental, and usage factors unique to each project. AKDO is not responsible for any effects that may be caused to products due to installation, wear from use, or exposure to environmental factors including but not limited to: hard water, chemicals, heat, flame, smoke, dirt or other substances. It is your responsibility to assess the project to determine if the product you are selecting is appropriate considering the unique characteristics of your installation, and to apply appropriate, high quality sealers when necessary. Please consult your installer for more information.

TECHNICAL DATA

FEATURES & STANDARD

DCOF - ANSI A. 137.1

SPECIFICATION

Due to the natural characteristics and variation in natural stone, slip resistance will vary. Such factors are dependent on lots, finish and the topical sealant applied. There is currently no standard industry test with the ability to measure the exact slip resistance.

In order to reduce the slipperiness of stone surfaces, AKDO suggests selecting a Non-Polished finish such as Honed, Sandblasted, or Textured stone, or choosing a mosaic, as the grout joints in the stone result in an increase of friction.